## PRODUCT ENVIRONMENTAL CARD

## Martela

242025

people

## **Product ID** Material weight Material emissions PodBooth Meeting (kg CO2e) (kg) 0.8 % л **□** − 0.1 % 0.8 % Meeting module for 1 to 4 г 0.1 % 1.6 0.2 Product code: 4178931 20.2 % 7,6 % Specifications: 411.3 975,31 Exterior surface (sides) upholstered Fabric 98% recycled polyester Door frame 90% recycled aluminium kg 1254,58 10,1 % Felt acoustic walls and ceiling Lightning and ventilation Recyclable package includes recycled kg CO2e 211.5 materials when available (plastic, carton). Wood (Form pressed or plywood) 11,1 % Glass Plastic (PA) Electrical parts Foam (PET 0% recycled) 12,4 % 11,4 % Metal (Steel) Plastic (PP) ■ Foam (PUR soft) Fabric (PE 100% recycled) Wood (Fiberboard) Metal (Aluminium recycled) Metal (Aluminium virgin) Rubber Fabric (Polyols 0% recycled) Designed with circular economy principles. Tested for safety and durability. This product is durable and has been designed following circular design strategies. Its technical durability complies with EN standard. Proper care and maintenance should be used to extend the product's lifespan. When no longer in use by the first customer, the product can be remanufactured, refurbished, or recovered. Any leftover materials that cannot be reused can be recycled or recovered as energy.



**Total emissions** 

1644,52 kg CO2e

Logistics 19.4 %

16.8 %



## CO2 emissions calculations are provided to offer a quick overview and are based on the brand's own self-assessment.

Martela's internal calculations cover the product's lifecycle from cradle-to-grave. Material weight does not include packaging. Emissions related to Materials cover the extraction and disposal phases. Emissions related to Logistics and Production are estimated based on Martela's own facility emissions. Logistics includes the transport of materials to Martela's production facilities and the transportation of the final product to the first customer. Production includes material waste and energy usage in 2024. These calculations are based on EN 15804+A2 standard using coefficients from LCA.no calculation tool. The calculation tool uses mainly Ecolovent 3.6 (2019) factors. More detailed calculations on selected products are available in EPD Norge portal in our official EPD documents.