

**Product** Scoop 865/42

**Test requested by** Martela Oyj, Takkatie 1, FI-00371, Helsinki

**Test specimen**

Top material	Aluminium
Frame	Steel
Leg	Steel



**Test method** Determination of strength, durability and safety of non-domestic table presented in the standard EN 15372: 2008 Furniture – Strength, durability and safety – Requirements for non-domestic tables. Selected type on usage was level 2.

Tests were carried out according to the standards below. Detailed test program with results is presented in pages 2-4.

**EN 15372:2008** Furniture. Strength, durability and safety. Requirements for non-domestic tables.

The test specimen was selected by Martela and arrived at Testing laboratory June 10, 2016. Tests were carried out August 15 – September 06, 2016 in temperature 15°C - 25 °C.

#### Assessment of results

Scoop 865/42 meets the strength, durability and safety requirements of a non-domestic tables presented in the standards EN 15372:2008 for level 2.

The test result is only valid to the specimen tested and no other.

This report may not be reproduced other than in full.

#### Martela Testing laboratory

Nummela, September 08, 2016

approved by:

Tero Karttunen  
Quality and Test Manager

tested by:

Jarno Forsman  
Laboratory Engineer

Ref.

Test report No.1357

Contact information:

Martela Oyj, Quality department, Tero Karttunen  
direct +358 (0)10 345 5123, email: [tero.karttunen@martela.fi](mailto:tero.karttunen@martela.fi)

EN 15372:2008 Furniture – Strength, durability and safety – Requirements for non-domestic tables			
Test Severity	Type of Use	Application	Test results
1	Light	Hotel bedroom, church, libraries	
2	General	general hotel, café, restaurant, public hall, banks, bars, meeting rooms	X
3	Severe	night-club, police station, transport terminals, hospital public areas, casino, homes for the elderly, sports changing rooms, prisons, barracks	

EN 15372:2008 Furniture – Strength, durability and safety – Requirements for non-domestic tables		
5 Safety requirements		RESULTS
(5.1) General	Edges of table tops which are directly in contact with the user are rounded or chamfered, and all other edges accessible during intended use are free from burrs and/or sharp edges.	OK
	Ends of hollow components are closed or capped.	OK
	Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided.	N/A
	It shall not be possible for any load bearing part of the table to come loose unintentionally.	OK
	All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use.	N/A
(5.2.1) Shear and squeeze points when setting up and folding	Unless 5.2.2 or 5.2.3 are applicable, shear and squeeze points that are created only during setting up and folding are acceptable.	OK
	The edges of parts moving relative to each other and creating shear and squeeze points shall be as specified in 5.1.	
(5.2.2) Shear and squeeze points under influence of powered mechanisms	There shall be no shear and squeeze points created by parts of the table operated by powered mechanisms, i.e. springs, gas lifts and motorized systems.	N/A
(5.2.3) Shear and squeeze points during use	There shall be no shear and squeeze points created by forces applied during normal use. There shall be no shear and squeeze points if a hazard is created by the user during normal movements and actions, e.g. attempting to move the table.	OK
<b>5.3 Stability</b>		
(5.3.1.1) General	Tables that can be set to heights both above and below 950 mm shall be tested to both 5.3.1.2 and 5.3.1.3.	
(5.3.1.2) Test for tables that are or can be set to a height of 950 mm or less	The table shall be set to the height most likely to overturn the table, but not more than 950 mm. The table shall not overturn when tested according to Clause 6.7 of EN 1730:2000 using the forces specified within Table 2.	OK

Ref.

Test report No.1357

Contact information:

Martela Oyj, Quality department, Tero Karttunen  
direct +358 (0)10 345 5123, email: tero.karttunen@martela.fi

(5.3.1.3) Test for tables that are or can be set to a height greater than 950 mm	The table shall be set to the height most likely to cause overturning, but not less than 950 mm. The table shall not overturn when tested according to Clause 6.7 of EN 1730:2000 using 50 % of the specified forces.	N/A
(5.3.2) Stability for tables with extension elements	The table shall not overturn when the vertical force specified is applied to the centre of the front of the table, through a loading pad.	N/A

EN 15372:2008 Furniture – Strength, durability and safety – Requirements for non-domestic tables					
Test	Loading	1	2	3	RESULTS
<b>1. Stability under vertical load</b> EN 1730:2000: 6.7	Test force, N				OK
	Main surface V <sub>1</sub>	<del>200</del>	200	<del>200</del>	
	V <sub>2</sub>	<del>400</del>	400	<del>400</del>	
	Ancillary surface V <sub>1</sub>	<del>100</del>	100	<del>100</del>	
V <sub>2</sub>	<del>200</del>	200	<del>200</del>		
<b>2. Stability for tables with extension elements</b> 5.3.2.	Test force, N	<del>200</del>	200	<del>200</del>	N/A
<b>3. Horizontal static load</b> EN 1730:2000: 6.2	Test force, N:				OK
	High (more than 600)	<del>400</del>	400	<del>600</del>	
Low (600 or less)	<del>200</del>	200	<del>300</del>		
10 times					
<b>4. Vertical static load</b> EN 1730:2000: 6.3	Test force, N:				OK
	a) main surface	<del>1000</del>	1250	<del>1250</del>	
b) ancillary surface	<del>200</del>	300	<del>300</del>		
10 times					
<b>5. Horizontal fatigue</b> EN 1730:2000: 6.4	Number of cycles: Test force 300N	<del>10 000</del>	15 000	<del>20 000</del>	OK
<b>6. Vertical fatigue for cantilever of pedestal tables</b> EN 1730:2000: 6.5	Number of cycles: Test force 300N	<del>10 000</del>	15 000	<del>20 000</del>	OK
<b>7. Vertical impact for tables without glass in their construction</b> EN 1730:2000: 6.6	Drop height, mm:				OK
	10 times	<del>180</del>	180	<del>240</del>	
<b>8. Vertical impact for tables with glass in their construction load</b> EN 1730:2000: 6.6  EN 14072:2003: 6 <sup>2)</sup>	Drop height, mm:				N/A
	10 times				
	Safety class <sup>1)</sup>	<del>180</del>	180	<del>240</del>	
Other class	<del>240</del>	240	<del>300</del>	N/A	

Ref.

Test report No.1357

Contact information:

Martela Oyj, Quality department, Tero Karttunen  
direct +358 (0)10 345 5123, email: tero.karttunen@martela.fi

9. Drop test for tables weighting more than 20 kg Annex A	Nominal drop height mm – tables without glass	100	100	100	N/A
	Nominal drop height mm – tables with glass	50	50	50	N/A
<b>DEFECTS AND OBSERVATIONS AFTER TEST PROCEDURE</b>	No defects after tests				

EN 15372:2008 Furniture – Strength, durability and safety – Requirements for non-domestic tables			
Requirements		Record	Result
(6.2) Strength and durability requirements	1) there are no fractures of any member, joint or component, 2) there are no loosening of joints intended to be rigid, 3) table fulfils its functions after removal of the test loads 4) table fulfils the stability requirements	Record whether the requirements are filled	OK

EN 15372:2008 Furniture – Strength, durability and safety – Requirements for non-domestic tables			
Requirements		Record	Result
7	Information for use shall be available in the language of the country in which it will be delivered to the end user. It shall contain at least the following details:  a) information regarding the intended use, see Annex C;  b) assembly instructions, where applicable;  c) instruction for the care and maintenance of the table.	Record whether the requirements are filled	N/A

End of report

Ref.

Test report No.1357

Contact information:

Martela Oyj, Quality department, Tero Karttunen  
direct +358 (0)10 345 5123, email: tero.karttunen@martela.fi